

### CHARACTERISTICS

Weight: 0,56 Kg / 1,24 Lb  
 Housing in Aluminium  
 Impeller in plastic UL 94 V-0  
 L-10 life expectancy at 40°C: 80.000 hours  
 Operating temperature range: -10 / +70 °C  
 Storage temperature: -40 / +70°C  
 Terminals  
 Impedance protected  
 IP20



### OPTIONS

Speed sensor  
 Other IP levels  
 Flying leads connection  
 Salt spray protection  
 Shocks and vibrations protection  
 Marine application  
 Wide temperature range  
 Other voltages

Part Number	Voltage	Frequency	Nb Phases	Airflow		Pressure		Nominal speed	Noise level LP	Nominal current	Starting current	Power	Capacitor
				l/s	CFM	mm H <sup>2</sup> o	inch H <sup>2</sup> o						
141LV02 82 010	115	50	1	23,5	49,82	1,9	0,075	1600	27,5	110	125	9	
	115	60	1	26	55,12	1,9	0,075	1700	28	100	110	8	
	220	50	1	23,5	49,82	1,9	0,075	1600	27,5	60	70	10	
	220	60	1	26	55,12	1,9	0,075	1700	28	55	65	9	
141LT02 82 010	115	50	1	33	69,96	4	0,157	2200	35	125	160	10	
	115	60	1	35	74,2	3,6	0,142	2400	38,5	110	140	9	
	220	50	1	33	69,96	4	0,157	2200	35	75	90	12	
	220	60	1	35	74,2	3,6	0,142	2400	38,5	65	75	10	
141LS02 81 010	115	50	1	42	89,04	8,5	0,335	2800	44,5	160	275	13	
	115	60	1	48	101,76	9,5	0,374	3200	49,5	140	240	12	
	220	50	1	42	89,04	8,5	0,335	2800	44,5	95	150	14	
	220	60	1	48	101,76	9,5	0,374	3200	49,5	80	130	12	

