

CHARACTERISTICS

Weight: 0,9 Kg / 1,99 Lb
 Housing in Aluminium
 Impeller in plastic UL 94 V-0
 L-10 life expectancy at 40°C: 80.000 hours
 Operating temperature range: -10 / +55 °C
 Storage temperature: -40 / +70°C
 Connection: Terminals
 GAM T1 listed
 VE/VP impedance protected;VK thermally protected
 IP20



OPTIONS

- Speed sensor
- Other IP levels
- Flying leads connection
- Salt spray protection
- Shocks and vibrations protection
- Marine application
- Wide temperature range
- Other voltages
- Three phases

Part Number	Voltage Frequency		Nb Phases	Airflow		Pressure		Nominal speed	Noise level LP	Nominal current	Starting current	Power	Capacitor
	V	Hz		l/s	CFM	mm H ² o	inch H ² o						
148VE0281030	220	50	1	49	103,88	4,5	0,177	1400	36	60	80	13	0,32
148VE0281030	220	60	1	58	122,96	6	0,236	1650	39	60	80	14	0,32
148VE0282030	115	50	1	49	103,88	4,5	0,177	1400	36	100	140	11	1
148VE0282030	115	60	1	58	122,96	6	0,236	1650	39	90	140	11	1
148VP0281030	220	50	1	82	173,84	8,3	0,327	2400	49	70	100	16	0,69
148VP0281030	220	60	1	70	148,4	5,4	0,213	2000	44	100	105	22	0,69
148VP0282030	115	50	1	81	171,72	7,3	0,287	2350	50	120	170	14	2,2
148VP0282030	115	60	1	70	148,4	5,6	0,220	2100	45,5	160	180	18	2,2
148VK0281030	220	50	1	100	212	18	0,708	2800	53	200	390	35	2,2
148VK0281030	220	60	1	117	248,04	21	0,826	3200	57	170	370	33	2,2
148VK0282030	115	50	1	100	212	18,7	0,736	2850	54	300	610	32	2,7
148VK0282030	115	60	1	119	252,28	24	0,945	3300	57	270	590	32	2,7

