

CHARACTERISTICS

Weight: 3,6 Kg / 7,96 Lb
Housing in Métal
Turbine in metal
L-10 life expectancy at 40°C: 25.000 hours
Operating temperature range: -10 / +70 °C
Storage temperature: -54 / +85°C
Connection: Leads
IP40



OPTIONS

Speed sensor
Other IP levels
Salt spray protection
Shocks and vibrations protection
Marine application
Wide temperature range
Other voltages
Safety switch

Part Number	Voltage V	Frequency Hz	Nb Phases	Airflow		Pressure		Nominal speed RPM	Noise level LP dBA	Nominal current A	Starting current A	power W	Capacitor µF
				l/s	CFM	mm H. o	inch H. o						
609COV016DC13	220	50	3	79,0	167,48	32	1,26	2800	65	0,26	1,25	60	
	380	50	3	79,0	167,48	32	1,26	2800	65	0,15	0,75	60	
	220	60	3	89,0	188,68	45	1,77	3200	68	0,30	1,15	88	
	380	60	3	89,0	188,68	45	1,77	3200	68	0,17	0,70	88	
	220	50	1	79,0	167,48	32	1,26	2800	65	0,29	1,10	66	4,7
	380	50	1	79,0	167,48	32	1,26	2800	65	0,16	0,65	66	1,47
609COV116DC13	220	60	1	89,0	188,68	45	1,77	3200	68	0,44	1,00	97	4,7
	380	60	1	89,0	188,68	45	1,77	3200	68	0,25	0,60	97	1,47
	220	50	3	79,0	167,48	32	1,26	2800	65	0,26	1,25	60	
	380	50	3	79,0	167,48	32	1,26	2800	65	0,15	0,75	60	
	220	60	3	89,0	188,68	45	1,77	3200	68	0,30	1,15	88	
	380	60	3	89,0	188,68	45	1,77	3200	68	0,17	0,70	88	
	220	50	1	79,0	167,48	32	1,26	2800	65	0,29	1,10	66	4,7
	380	50	1	79,0	167,48	32	1,26	2800	65	0,16	0,65	66	1,47
	220	60	1	89,0	188,68	45	1,77	3200	68	0,44	1,00	97	4,7
	380	60	1	89,0	188,68	45	1,77	3200	68	0,25	0,60	97	1,47

