

### CHARACTERISTICS

Weight: 4,2 Kg / 9,28 Lb  
 Housing in Aluminium  
 Impeller in metal  
 L-10 life expectancy at 40°C: 25.000 hours  
 Operating temperature range: -10 / +70 °C  
 Storage temperature: -54 / +85°C  
 Connection: Leads  
 GAM T1 listed  
 IP40



### OPTIONS

- Speed sensor
- Other IP levels
- Salt spray protection
- Shocks and vibrations protection
- Marine application
- Wide temperature range
- Other voltages
- Safety switch
- Terminal block
- NATO Codification (not on all part numbers, please consult the factory for more detailed information)

Part Number	Voltage V	Frequency Hz	Nb Phases	Airflow		Pressure		Nominal speed RPM	Noise level LP dBA	Nominal current A	power W	Capacitor µF
				l/s	CFM	mm H. o	inch H. o					
62GP016DC13 A	230	50	3	190,0	402,80	31,1	1,22	2930	67	0,29	46	
	400	50	3	190,0	402,80	31,1	1,22	2930	67	0,17	46	
	230	60	3	230,0	487,60	42,83	1,69	3450	71,5	0,25	61	
	400	60	3	230,0	487,60	42,83	1,69	3450	71,5	0,15	61	
	230	50	1	190,0	402,80	31,1	1,22	2930	67	0,28	45	3,2
	400	50	1	190,0	402,80	31,1	1,22	2930	67	0,17	45	1
	230	60	1	230,0	487,60	42,83	1,69	3450	71,5	0,28	62	3,2
	400	60	1	230,0	487,60	42,83	1,69	3450	71,5	0,16	62	1

