

CHARACTERISTICS

Weight: 4,75 Kg / 10,5 Lb
Housing in Aluminium
Turbine in plastic
L-10 life expectancy at 40°C: 25.000 hours
Operating temperature range: -10 / +70 °C
Storage temperature: -54 / +85°C
Connection: Leads
IP40



OPTIONS

Speed sensor
Other IP levels
Salt spray protection
Shocks and vibrations protection
Marine application
Wide temperature range
Other voltages
Safety switch

Part Number	Voltage V	Frequency Hz	Nb Phases	Airflow		Pressure		Nominal speed RPM	Noise level LP dBA	Nominal current A	Starting current A	power W	Capacitor µF
				l/s	CFM	mm H. o	inch H. o						
692CCP016DC13	220	50	3	38,0	80,56	64	2,52	2850	68	0,35	1,75	67	
	380	50	3	38,0	80,56	64	2,52	2850	68	0,20	1,00	67	
	220	60	3	44,0	93,28	90	3,54	3350	73	0,31	1,65	88	
	380	60	3	44,0	93,28	90	3,54	3350	73	0,18	0,95	88	
	220	50	1	38,0	80,56	64	2,52	2850	68	0,35	1,50	65	4,7
	380	50	1	38,0	80,56	64	2,52	2850	68	0,20	0,90	65	1,47
692CCP116DC13	220	60	1	44,0	93,28	90	3,54	3350	73	0,42	1,40	92	4,7
	380	60	1	44,0	93,28	90	3,54	3350	73	0,24	0,80	92	1,47
	220	50	3	38,0	80,56	64	2,52	2850	68	0,35	1,75	67	
	380	50	3	38,0	80,56	64	2,52	2850	68	0,20	1,00	67	
	220	60	3	44,0	93,28	90	3,54	3350	73	0,31	1,65	88	
	380	60	3	44,0	93,28	90	3,54	3350	73	0,18	0,95	88	
	220	50	1	38,0	80,56	64	2,52	2850	68	0,35	1,50	65	4,7
	380	50	1	38,0	80,56	64	2,52	2850	68	0,20	0,90	65	1,47
	220	60	1	44,0	93,28	90	3,54	3350	73	0,42	1,40	92	4,7
	380	60	1	44,0	93,28	90	3,54	3350	73	0,24	0,80	92	1,47

