

CHARACTERISTICS

Weight: 2,1 Kg/4,64 Lb
 Housing in Aluminium
 Impeller in plastic
 L-10 life expectancy at 40°C: 25.000 hours
 Operating temperature range: -10 / +70 °C
 Storage temperature: -54 / +85°C
 Connection: Leads
 IP40



OPTIONS

Speed sensor
 Other IP levels
 Salt spray protection
 Shocks and vibrations protection
 Marine application
 Wide temperature range
 Other voltages
 Safety switch
 Aluminium impeller
 NATO Codification (not on all part numbers, please consult the factory for more detailed information)

Part Number	Voltage V	Frequency Hz	Nb Phases	Airflow		Pressure		Nominal speed RPM	Noise level LP dBA	Nominal current A	Starting current A	power W	Capacitor µF
				l/s	CFM	mm H. o	inch H. o						
85CB01/26DC13	220	50	3	75,0	159,00	16	0,63	2850	57	0,11	0,32	20	
	380	50	3	75,0	159,00	16	0,63	2850	57	0,07	0,19	20	
	220	60	3	88,0	186,56	21	0,83	3300	61	0,10	0,30	23	
	380	60	3	88,0	186,56	21	0,83	3300	61	0,06	0,18	23	
	220	50	1	75,0	159,00	16	0,63	2850	57	0,11	0,26	20	1,47
	380	50	1	75,0	159,00	16	0,63	2850	57	0,07	0,15	20	0,47
86CB01/26DC13	220	60	1	88,0	186,56	21	0,83	3300	61	0,12	0,25	24	1,47
	380	60	1	88,0	186,56	21	0,83	3300	61	0,07	0,15	24	0,47
	220	50	3	111,0	235,32	16	0,63	2800	56	0,17	0,47	35	
	380	50	3	111,0	235,32	16	0,63	2800	56	0,10	0,28	35	
	220	60	3	127,0	269,24	22	0,87	3200	60	0,15	0,44	41	
	380	60	3	127,0	269,24	22	0,87	3200	60	0,09	0,26	41	
	220	50	1	111,0	235,32	16	0,63	2800	56	0,18	0,40	34	2,2
	380	50	1	111,0	235,32	16	0,63	2800	56	0,11	0,24	34	0,69
	220	60	1	127,0	269,24	22	0,87	3200	60	0,20	0,38	42	2,2
	380	60	1	127,0	269,24	22	0,87	3200	60	0,12	0,22	42	0,69

