



DC AXIAL

Size		Voltage	Free airflow		Maximum pressure		Noise level	Norms and directives	Image	Part numbers
80 x 80 x 25 mm	3,15 x 3,15 x 1 "	12V	14,88l/s	31,55CFM	4,45mmH2O	0,18inchH2O	34,2dBA	CE UL RoHS		146DH-S
		12V- 24V - 48V	22l/s	46,64CFM	10,89mmH2O	0,43inchH2O	44dBA	CE UL RoHS		
92 x 92 x 38 mm	3,62 x 3,62 x 1,5 "	24V	31,4l/s	66,57CFM	20,19mmH2O	0,79inchH2O	51,8dBA	-		99YH-S
			35,3l/s	74,84CFM	23,96mmH2O	0,94inchH2O	54,6dBA	-		
120 x 120 x 32 mm	4,72 x 4,72 x 1,26 "	12V - 24V - 48V	27l/s	57,24CFM	2,24mmH2O	0,09inchH2O	29,5dBA	CE UL RoHS		158D
			39l/s	82,68CFM	4,79mmH2O	0,19inchH2O	37,5dBA	CE UL RoHS		
			49l/s	103,88CFM	7,44mmH2O	0,29inchH2O	42,5dBA	CE UL RoHS		
			55,9l/s	118,51CFM	9,69mmH2O	0,38inchH2O	45,5dBA	CE UL RoHS		
120 x 120 x 38 mm	4,72 x 4,72 x 1,5 "	110V	49l/s	103,88CFM	7,44mmH2O	0,29inchH2O	42,5dBA	-		125DH
120 x 120 x 38 mm	4,72 x 4,72 x 1,5 "	12VDC	46l/s	97,52CFM	8mmH2O	0,31inchH2O	45dBA	CE RoHS		125YG
		24VDC	46l/s	97,52CFM	8mmH2O	0,31inchH2O	45dBA	CE RoHS		
		48VDC	46l/s	97,52CFM	8mmH2O	0,31inchH2O	45dBA	CE RoHS		
120 x 120 x 38 mm	4,72 x 4,72 x 1,5 "	12V - 24V - 48V	27l/s	57,24CFM	2,52mmH2O	0,1inchH2O	30dBA	CE RoHS		125D_A
			39l/s	82,63CFM	5,27mmH2O	0,21inchH2O	38dBA	CE RoHS		
			49l/s	103,81CFM	8,32mmH2O	0,33inchH2O	43dBA	CE RoHS		
			53l/s	112,29CFM	9,75mmH2O	0,38inchH2O	46,2dBA	CE RoHS		
			61,10l/s	129,45CFM	13,52mmH2O	0,53inchH2O	48,8dBA	CE RoHS		
			69,44l/s	147,12CFM	19,21mmH2O	0,76inchH2O	52,6dBA	CE RoHS		
172 x 150 x 38 mm	6,77 x 5,9 x 1,5 "	12V	110l/s	233,2CFM	12,5mmH2O	0,49inchH2O	57dBA	CE UL RoHS		121D-148D
			105l/s	222,6CFM	22,5mmH2O	0,89inchH2O	62dBA	CE UL RoHS		
		24V	112l/s	237,44CFM	12mmH2O	0,47inchH2O	58dBA	CE UL RoHS		
			120l/s	254,4CFM	32,51mmH2O	1,28inchH2O	66dBA	CE UL RoHS		
			120l/s	254,4CFM	32,5mmH2O	1,28inchH2O	66dBA	CE UL RoHS		
		28V	120l/s	254,4CFM	32,5mmH2O	1,28inchH2O	66dBA	CE UL RoHS		
		48V	112l/s	237,44CFM	12mmH2O	0,47inchH2O	58dBA	CE UL RoHS		
		110V	112l/s	237,44CFM	12mmH2O	0,47inchH2O	58dBA	CE UL RoHS		